



1.3

Taurus

Hydraulic platform Lift for vehicles with passengers in compliance with the Machine directive.

Advantages

Flexibility: Integrated power unit and control panel inside the shaft (MRL).

Comfort: Movement through T-profile lift guides, low pressure side acting 2:1 piston. This provides a smoother and less noisy ride.

Safety: Calculations in accordance with EN81.20 Standard. Downwards double safety valve. Rupture valve in accordance with EN81.20. Instantaneous safety gear on car frame. Minimum pressure safety valve. Safety light curtains. A safety level equivalent to that of any lift.

Adaptability: Adjustable wheel distance with different heights to facilitate loading and unloading of the vehicle.

► Applications

Vehicles
Residenciales

Standard sizes

Q (kg)	SW	SD	CW	CD	CO
2500	2950	5460	2450	5400	2350

SW: Shaft Width
SD: Shaft Depth
CW: Cabin Width

CD: Cabin Depth
CO: Clear Opening

► Taurus Lift Use

Options:

Hörmann sectional doors.
Remote controls.
Side handrails.

Car lighting.
Integrated or standard phone.

Technical features

Duty load(Kg)	2500 kg.
Duty speed	0,15 m/s
Stops	up to 4 stops
Roping	2:1 (with a single side piston)
Standard pit	350 mm.
Maximum travel	10m
Mínimum headroom	2200 mm.
Maximum power	9,5 kw



For other configurations or shaft sizes, please consult us.



► Taurus door finishes:

11 colours, same price

